NOT APPLICABLE TO INTERPLANT SHIPMENTS (A)

| SPECIAL PACKAGING INSTRUCTION(SPI) (A) NATIONAL STOCK NUMBER 5965-01-443-5490 | | | | | | | | | | | |
|--|---------------------------------------|--|---------------|--------------|-------------------|---------------|--------|---------------|--------------|-------------------|----------------|
| NOMENCLATURE | | | | | | UI | Q | UP | | SPI NUMB | , . |
| MICROPHONE CABLE | | | | | | EA | | 1 | | PM22442-3 | 6-5 |
| Cleaning & Drying shall be | in accord | | | D-2073- | 1 | | _ | | _ | | |
| MILITARY PRESERVATION | STEPS | DRAWING OR SPECIFICATIO | | STYLE | TYPE | GRA | DE | CLASS | | SIZE AND REM | IARKS |
| REQUIREMENT (MIL-STD-2073-1, Method 30 | SIEPS | SPECIFICATIO | 'IN | SIILE | IIFE | GRA | DE | CLAS | | (INCHES) | IAICIO |
| Container (bag) | (B)(C)1 | MIL-DTL- | 117 | 2 | I11 | | | В | | 4 x 6 x 0.004 THK | |
| Closure | (D)(E)(F)2 | | | | . " | | | | | Tape or Heat S | eal |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | \bot | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | _ | | |
| | | <u> </u> | _ | | | | | | | | |
| INTERMEDIATE PACKAC | | | | MARKIN | | • • • | 3.477 | · cm | | 100 | |
| In accordance with MII | L-STD- | 2073-1 | | In acc | ordano ecified | | | 51 |) –. | 129 | |
| As specified hereon. | 1.77 | SOUTH OF THE STATE | | | ecmea | nere | OII. | | | | |
| QUALITY PERFORMANG In accordance with MII | E and Th | ESTING REQUI | IKE | MEN 15 | | | | | | | |
| As specified hereon. | | | | | | | | | | | |
| Specifications, standared ar | | | in el | ffect on da | te of i | nvitati | ion fo | r bid f | orn | a part of this | |
| Packaging Instruction, Requ | uirements | of MIL-STD- | 207 | 3-1 and N | AIL-S | TD- | 1916 | are pa | rt o | f this packaging | |
| instruction. Unless otherwis | se specifie | d, material will b | be m | iinimum si | ze IAV | V MII | L-ST | D-20 | 73- | -1. | |
| Tolerances shall be in accor | dance wit | h material specif | ficat | ions, unles | s othe | rwise | specif | fied he | ereo | n. | |
| | UN | IT PACK LOGIS | STIC | CS DATA | (Appr | oxima | te un | | | | |
| WEIGHT (POUNDS) | | CUBE (CUBI | | | | | | | | | |
| .04 lbs | | .003 cu. | | | | | | | | | |
| REMARKS/ALL DIMENS | IONS AR | E IN INCHES U | JNL | ESS OTE | IERWI | SE SI | PECI | FIED. | | | |
| | | - | | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | _ |
| (A) — This SPI is <u>no</u> | t <mark>applic</mark> a | able for Interp | lan | t or com | <u>nercia</u> | <u>al shi</u> | pme | <u>nts.</u> F | ack | aging and mark | ing for inter- |
| plant shipmeı | nt is for s | upplies and ma | ater | rials that | do no | t dire | ctly | enter | the | militarysupply | system. Typi- |
| cal interplant | : shipme | nts are shipme | ents | from a | vendo | r to a | a sub | conti | act | or or a prime o | ontractor, or |
| between cont | ractors a | ind subcontrac | ctor | s, or from | n a ve | ndor | or c | ontra | cto | r to a military a | rsenai, piani, |
| or other activity for evaluation, immediate use, or further processing as specified in the applicable | | | | | | | | | | | |
| contract. | | | | | | | | | | | |
| (B) — Coil cable to fit specified bag (step 1) and while holding coil, insert into specified bag and close | | | | | | | | | | | |
| (step 2). | | | | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| Original Preparer: J. D. Stallings / Dec 95 Revised by: R Poole Date: 17 MAR 2003 | | | | | | | | | | | |
| | of Preparer: J. D. Stallings / Dec 95 | | | Re | Revised by: R Poo | | ole | рате: | I / WAK ZUUS | | |
| ITEM DATA (APPROX) | | SBCCON | / 1 81 | 1361 | | | | | | | |
| ITEM CODE - 123 | | AMSSB-RE | N | SF-PK | | | | | | | |
| ITEM SIZE - 1 1/4 x 1 1/4 x | 5/8 | , | | J_ ' ' ' | R | p 1 | 23-0 | 092-0 | 01 | Α | 16 APRIL 2003 |
| ITEM WEIGHT03 lbs | | PAGE NUMBER | NUN | ABER OF PAGE | | _ | | 034 - 0 | | 123-029 | 8 JAN 2002 |
| I I EWI WEIGHI — .U3 IDS | . | 1 | | 3 | <u> </u> | | PRO | | | REVISION | DATE |

| SPECIAL PACKAGING INSTRUCTION | NATIONAL STOCK NUMBER 5965-01-443-5490 | | | | |
|-------------------------------|--|-----------------------------------|--|--|--|
| NOMENCLATURE MICROPHONE CABLE | PAGE NUMBE 2 of 3 | R SPI NUMBER (PN) PM22442-36-5 | | | |

- (C) Bag to be constructed of A—A—3174 material, as specified in MIL—DTL—117. Closure shall be accomplished by tape or heat seal. When using tape, tape shall not come into contact with the microphone cable. When using a heat seal, heat seal in accordance with the bag or material supplier is recommendations for dwell, pressure and temperature requirements. Heat seal test is not required.
- (D) Trapped air shall be kept to a minimum by compressing the bag or by a mechanical evacuation process to the extent practicable, prior to accomplishing the final heat seal. Do not evacuate to the point of damaging or deforming the item
- (E) Packaging Quality Assurance Provisions (PQAP).

Part I - Applicable Documents

Military standards

MIL-STD-1916 - Department Of Defense Test Method Standard

MIL-STD-2073-1- Standard Practice For Military Packaging

Part II - Packaging Quality Provisions.

1. First Article Inspection. The first article packaging sample shall consist of 5 microphone cables (MIL-DTL-22442/36); however, the sample shall be packaged as specified herein.

Note: when the packaging sample is produced at the same time as the cable assemblies, the packaging sample shall be pulled from that sample of cable assemblies.

If required, special sampling, inspection and acceptance criteria are contained in Part III of this PQAP and inspected for compliance with any or all of the requirements of this SPI.

a. Acceptance Criteria. If any first article sample fails to comply with any of the requirements, the first article packaging sample shall be rejected. The Government reserves the right to terminate inspection upon any failure to comply with any of the requirements. The contractor shall obtain written approval from the contracting activity prior to proceeding with regular production.

2. Conformance Inspection.

- a. Lotting. A lot shall consist of the items produced by one manufacturer, at one plant, from the same materials, under the same manufacturing conditions, and at essentially the same time. However; when the packaging sample is produced at the same time as the cable assemblies, lotting shall be in accordance with lotting for the Conformance Inspection of the cable assemblies.
- **b. Sampling.** Sampling shall be conducted in accordance with the attributes sampling plan of MIL-STD-1916 using the verification levels (VLs) specified herein.
- **c. Inspection.** Inspection shall consist of examination and test of all the characteristics contained in Part III and Part IV of this PQAP.

SPECIAL PACKAGING INSTRUCTION

NATIONAL STOCK NUMBER 5965-01-443-5490

NOMENCLATURE MICROPHONE CABLE

3 of 3

PAGE NUMBER SPI NUMBER (PN) PM22442-36-5

3. Inspection Equipment Coding.

VI = Visual inspection

CE = Commercial inspection equipment

PART III – INSPECTION REQUIREMENTS

PACKAGING CHARACTERISTICS

| CATEGORY | CHARACTERISTICS | SAMPLING and ACCEPTANCE CRITERIA | INSPECTION METHOD |
|----------|---|----------------------------------|-------------------|
| Critical | None Defined. | | |
| Major | None Defined. | | |
| Minor | | | |
| 101 | Item completely clean and dry prior to unit packing. | VL-III | VI |
| 102 | Container (bag) evident and correct. | VL-III | VI and CE |
| 103 | Unit pack container (bag) and closure evident and correct. | VL-III | VI and CE |
| 104 | Unit pack container (bag) marking evident, correct and legible. | VL-III | VI and CE |

NOTES:

VI = Visual inspection

CE = Commercial inspection equipment

PART IV - CERTIFICATION REQUIREMENTS

Certification shall be required for each characteristic specified below and shall include actual examination and test results when required herein. Results of examinations and tests shall be on file at the contractor s facility and shall be available to the Government for review.

NUMBER

CHARACTERISTIC

TO COMPLY WITH

401

Packaging material

Applicable specification or standard specified in this SPI.